



## Modelos normalizados, gama SRV

Mantas calefactoras flexibles para curado de composites, con tecnología de vacío EASYSeal

### Modelos rectangulares

Código	Dimensiones en mm		Zona calefactora		Wattios
	Ancho	Largo	Ancho	Largo	
SRV5-240-6X6-S-A	229	305	152	152	180
SRV5-240-6X12-S-A	229	457	152	305	360
SRV5-240-6X24-S-A	229	762	152	610	720
SRV5-240-8X8-S-A	279	356	203	203	320
SRV5-240-10X10-S-A	330	406	254	254	500
SRV5-240-12X12-S-A	381	457	305	305	720
SRV5-240-12X24-S-A	381	762	305	610	1440
SRV5-240-16X16-S-A	483	559	406	406	1280
SRV5-240-18X18-S-A	533	610	457	457	1620
SRV5-240-24X24-S-A	686	762	610	610	2880



### Modelos redondos

Código	Dimensiones en mm	Zona calefactora	Wattios
	Diámetro	Diámetro	
SRV5-240-6D-S-A	Ø152	Ø305	140
SRV5-240-8D-S-A	Ø203	Ø356	250
SRV5-240-10D-S-A	Ø254	Ø406	395
SRV5-240-12D-S-A	Ø305	Ø457	565
SRV5-240-16D-S-A	Ø406	Ø559	1005
SRV5-240-20D-S-A	Ø508	Ø660	1570
SRV5-240-24D-S-A	Ø610	Ø762	2270